

Product No: 251400115M10H001B2000

**BD SENSORS DMK331 P.TRANSMITTER 4.0BAR 4-20MA/2W 0.5%
ACC MALE PLUG12X1 4PIN G1/2" FKM PVDF
251400115M10H001B2000**

FEATURES

- Pressure port G 1/2" flush for pasty and polluted media.
- Pressure port G 1/2" open port PVDF for aggressive media.



General Information

Brand	BD SENSORS
Product Series	DMK 331
Product Type	Ceramic Sensor
Version	Standard

Technical Attributes

Accuracy	0.5 % FSO
Application	Plant and machine engineering. Energy industry. Environmental engineering (water - sewage - recycling). Medical technology (Specially for oxygen application).
Electrical Connection	Male plug M12x1 (4-pin) / metal
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	4.0
Mechanical Connection	G1/2" DIN 3852 open pressure port
Mechanical Stability	Vibration: 10 g RMS (25 ... 2000 Hz) according to DIN EN 60068-2-6. Shock: 500 g / 1 msec according to DIN EN 60068-2-27.
Operational Life	100 million load cycles

Permissible Temperatures	Medium: -40 ... 125 °C Electronics / Environment: -40 ... 85 °C Storage: -40 ... 100 °C
Pressure Port	PVDF (PVDF only with G1/2" DIN 3852 open pressure port (up to 60 bar); permissible medium temperature: -30 ... 60 °C)
Response Time (ms)	≤ 10
Seals	FKM

Physical Attributes

Diaphragm Material	Ceramics Al ₂ O ₃ 96 %
--------------------	--

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------