

Product No: MSB108030G

IDE IDE66 ROLLED MILD STEEL SINGLE DOOR WALL MOUNTED ENCLOSURE 1000Hx800Wx300Dmm GREY MSB108030G

FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- Primer coated and hardened RAL 7035 polyester paint, embossed, with UV protection
- - Substitute G with A for orange colour RAL 2008
- - Mounting plate included



| General Information | |
|-----------------------|--|
| Brand | IDE |
| Customs Tariff Number | 85.38.10.00 |
| EAN | 8431044491509 |
| ETIM 8.0 | EC000261 |
| Product End of Life | It does not require specific recycling operations. |
| Product Type | Wall-mounting Cabinet |

| Technical Attributes | |
|---------------------------------|--|
| Application | Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts. |
| Maximum Operational Voltage (V) | 1000 AC / 1500 DC |

| Physical Attributes | |
|--------------------------------|--|
| Ambient Temperature Range (°C) | -25 to +60 |
| Cable Entry (mm) | 125H x 685W |
| Colour | RAL 7035 |
| Door Profiles | 2 |
| Door Type | Single |
| Finish | Coated with primer, and hardened polyester paint, textured, with UV protection |
| Installation | Surface |



| Lock Type | 5-mm double-bit lock - One 3-point lock |
|----------------------------------|--|
| Material | Cold-rolled steel EN 10130+A1 |
| Maximum Cabinet Load (kg) | 390 |
| Maximum Door Load (kg) | 40 |
| Maximum Mounting Plate Load (kg) | 350 |
| Mounting Plate | With flat mounting plate. 2-mm galvanised sheet steel |
| No. of Hinges | 3 |
| No. of Locks | 3 points |
| Sealing Gasket | Injected polyurethane sealing gasket |
| Supply | Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied assembled inside the cabinet. |
| Type of Door | Single opaque door. Reversible |
| Wall Fixing (mm) | 960H x 560W |

| Dimensions | |
|----------------------------|---|
| Dimensions (mm) | 1000H x 800W x 300D |
| Mounting Plate Size (mm) | 970W x 750H |
| Thickness (mm) | Enclosure: 1.5 Door: 2 Cable entry lid: 2 |
| Usable Internal Space (mm) | 950H x 750W x 279D |
| Weight (kg) | 53.2 |

| Protection & Standards | |
|---------------------------|------------------------|
| Certifications | UL508A |
| Degree of Protection | IP66 |
| Directive | 2014/35/EU |
| NEMA Degree of Protection | NEMA 1, 12, 4 |
| Rated Impact Resistance | IK10 |
| Standards | IEC 62208, IEC 61439-1 |
| Sustainability | Rohs - Reach |
| | |



| Resources | |
|------------------------------|--------------------|
| Product catalogue (Flipbook) | Download from here |