

## Product No: UNO-QRD-230VAC

### ORBIS ANALOG TIME SWITCH D/15MIN 1NO 16A UNO-QRD-230VAC

#### FEATURES

- - 16A/250V AC switching
- - Backlit Display
- - Manual Override
- - Simple Programming
- - Display of operating schedule and relay status
- - Australia daylight savings time
- - 24 hour or 7 days program



#### General Information

|              |             |
|--------------|-------------|
| Brand        | ORBIS       |
| Product Type | Time Switch |

#### Technical Attributes

|                                      |         |
|--------------------------------------|---------|
| Battery Backup                       | 150 hrs |
| Contacts                             | 1NO     |
| Function                             | Daily   |
| Maximum Switching Current (A)        | 16      |
| Maximum Switching Voltage AC (V)     | 250     |
| Minimum Switching Time (s)           | 900     |
| No. of Switching Intervals           | 96 pins |
| Nominal Frequency (Hz)               | 50/60   |
| Power Consumption (W)                | 0.5     |
| Rated Current (A)                    | 16      |
| Rated Impulse Withstand Voltage (kV) | 2.5     |
| Rated Supply Voltage AC/DC (V)       | 230V AC |
| Terminal Type                        | Screw   |
| Universal Supply Voltage AC (V)      | 230     |

#### Physical Attributes

|                                    |            |
|------------------------------------|------------|
| Mounting Type                      | DIN Rail   |
| Operational Temperature Range (°C) | -10 to +45 |

### Dimensions

|                |   |
|----------------|---|
| No. of Modules | 1 |
|----------------|---|

### Protection & Standards

|                      |      |
|----------------------|------|
| Degree of Protection | IP20 |
| Pollution Degree     | 2    |

### Resources

|                              |                                    |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | <a href="#">Download from here</a> |
|------------------------------|------------------------------------|