

ABB OXB200E3S3QTEG TRUONE® ATS MILD STEEL ENCLOSED 3P+N 200A LEVEL 3 IP65

OXB200E3S3QTEG

FEATURES

- RAL 7035 Grey.
- 1.6mm thickness mild steel.
- Concealed and removable hinges with pins.
- Polyurethane sealing gaskets.
- Top and bottom glandplates.
- Switched Neutral.
- Operation temperature (-25 to 70°C).
- Voltage (200-480 VAC with +/- 20% tolerance).
- Tolerant of: Vibrations (acc. IEC 60068-2-6), Shocks (acc. IEC 60068-2-27).



GENERAL INFORMATION

Brand	ABB
Product Type	Truone® Automatic - Enclosed

TECHNICAL ATTRIBUTES

No. of Poles	3P + N
Rated Current (A)	200
Rated Operational Voltage AC (V)	200-480
Transition Type	Delayed

PHYSICAL ATTRIBUTES

Colour	Grey, RAL7035
Material	Mild Steel

DIMENSIONS

Dimensions (mm)	800H x 300D x 600W
-----------------	--------------------

PROTECTION & STANDARDS

Degree of Protection	IP65
----------------------	------

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

DIMENSIONS

