

CA724/2



**connectwell**  
THE RIGHT CONNECTION

### Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4 and 10 pole assemblies and are ready for immediate installation.

#### PRODUCT SPECIFICATION

|               |        |
|---------------|--------|
| Rated Current | 57 A   |
| Torque        | 0.5 Nm |

#### ORDERING INFORMATION

| CAT. NO. | DESCRIPTION   | STD. PACK |
|----------|---|-----------|
| CA724/2  | Pre Assembled Shorting Link assemblies with 2 poles   | 100       |
| CA724/3  | Pre Assembled Shorting Links assemblies with 3 poles  | 50        |
| CA724/4  | Pre assembled Shorting Link assemblies with 4 poles   | 50        |
| CA724/10 | Pre Assembled Shorting Links assemblies with 10 poles | 100       |
| CA724/9  | Pre Assembled Shorting Links assemblies with 9 poles  | 100       |

#### SUITABLE FOR

|           |   |
|-----------|---|
| CTS10UV0  | 10 sq. mm Feed Through Terminal Blocks          |
| CTS10     | 10 sq.mm Standard Feed Through Terminal Blocks. |
| CTS10CR   | 10 sq.mm Standard Feed Through Terminal Blocks. |
| CTS10U EX | 10 sq. mm Feed Through Terminal Blocks          |
| CTS10U    | 10 sq. mm Standard Feed Through Terminal Blocks |