

PRODUCT-DETAILS

# E1.2N 1250 Ekip Touch LSIG 3p WMP

## E1.2N 1250 Ekip Touch LSIG 3p WMP



### General Information

Extended Product Type	E1.2N 1250 Ekip Touch LSIG 3p WMP
Product ID	1SDA072196R1
EAN	8015644760465
Catalog Description	E1.2N 1250 Ekip Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2N 1250 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

### ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

### Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

## Eco Transparency

---

Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028
---	------------------------------------

---



---

## Environmental

---

Environmental Information	9AKK10103A1038 9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---



---

## Ordering

---

Order Code US and Canada	Z1NREHAF000A000000XX
EAN	8015644760465
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

---



---

## Dimensions

---

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	18 kg

---



---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644760465

---



---

## Additional Information

---

Current Type	AC
Electrical Durability	U <sub>e</sub> =< 440 V 8000 cycle U <sub>e</sub> = 500 ... 690 V 6500 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	244 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cs</sub>	100 %
Rated Current (I <sub>n</sub> )	1250 A
Rated Voltage (U <sub>r</sub> )	690 V
Rated Impulse Withstand	acc. to IEC 60947-2 12 kV

Voltage ( $U_{imp}$ )	
Rated Insulation Voltage ( $U_i$ )	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 50 kA for 3 s 30 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current ( $I_U$ )	1250 A
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Version	W
CAD Dimensional Drawing	1SDH001252R0024

## Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000999R0103
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

## Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

