

Product No: OT100F3

ABB OT100F3 SWITCH-DISCONNECTOR OT100F3

FEATURES

- Front operated, 3 pole switch disconnecter
- Base mounted, DIN-rail mountable
- Non-fusible disconnect switch with front protected clamp terminals
- Switches operating mechanism on top of the switch
- Degree of protection: Front IP20



General Information

Brand	ABB
Product Type	Manual
Suitable For	Distribution Board Installation
Type	Main Switch

Technical Attributes

Conventional Free-Air Thermal Current - I _{th} (A)	115
Conventional Thermal Current - I _{the} (A)	115
Main Circuit Electrical Connection	Screw Connection
Maximum Operational Voltage AC (V)	750
Mode of Operation	Front Operated
No. of Poles	3
Operating Mechanism	Mechanism on Top of the Switch
Power Loss (W)	4/Pole
Product Quantity	10
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 415V (A)	100
Rated Operational Current AC-22A 380-415V (A)	100
Rated Operational Current AC-22A 500V (A)	100
Rated Operational Current AC-22A 690V (A)	100

Rated Operational Current AC-23A 380-415V (A)	80
Rated Operational Current AC-23A 500V (A)	60
Rated Operational Current AC-23A 690V (A)	40
Rated Operational Power AC-23A 380-415V (kW)	37
Rated Operational Power AC-23A 400-415 V (kW)	37
Rated Operational Power AC-23A 500V (kW)	37
Rated Operational Power AC-23A 690V (kW)	37
Rated Operational Voltage (V)	750
Rated Short-Time Withstand Current - I _{cw} (kA)	2.5
Rated Short-time Withstand Current - I _{cw} (kA/1s)	2.5
Rated Uninterrupted Current - I _u (A)	115
Terminal Type	Screw Terminals

Physical Attributes

Control Element Colour	Black
Mounting Type	Base Mount

Dimensions

Cable Cross Section (mm ²)	10 - 70
Dimensions (mm)	70W x 100H x 74D

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3
Standards and Approvals	IEC 60947-3 / UL 98 / CSA C22.2 NO.4

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------