

Product No: DBM1760FM

DEHN COORD. LIGHTN. CURRENT ARRESTER TYPE 1 DEHNBLOC DBM 1760 FM, VP, IEC DBM1760FM

FEATURES

- Coordinated single-pole lightning current arrester
- Width: 2 modules
- Type 1 SPD according to EN 61643-11
- With remote signalling contact
- RADAX Flow spark gap technology
- Follows current limitation
- Fault indication
- Energy-coordinated according to IEC 62305-4



General Information

Article No.	961175
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Follow Current Extinguishing Capability AC (kArms)	25
Integral Fuse	No
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25
Maximum Continuous Operating Voltage MCOV AC (V)	760
No. of Poles	1P+PE
Nominal Discharge Current (8/20 μ s) - In (kA)	25
Nominal Voltage AC (V)	690
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Signal C/O Contact	Yes
Voltage Protection Level - Up (kV)	≤ 4

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.12W x 0.21L x 0.08D
No. of Modules	2
Weight (kg)	0.59

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------