

Product No: SLA4.100

PULS AS-INTERFACE POWER SUPPLY 30.5V DC, 4A SLA4.100

FEATURES

- 115 / 230V Switchable input
- Efficiency up to 90%
- AS-Interface decoupling network included
- Supports IR-Addressing mode
- Full output power between -10 and +60°C



General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85044083
E Classification	E-CS01
Product Type	AS-Interface
Range	SilverLine
Series	SL series
Warranty Period (Months)	36

Technical Attributes

AC Input Type	Manual-select
Connection Type	Screw terminals
Derating	3 W/°C
Derating Temperature (°C)	> +60
Efficiency	88.00%
Input Inrush Current Limitation	NTC
Input Voltage Range AC (V)	100-120, 200-240
Integrated Decoupling Function	No
Maximum Ripple and Noise Voltage (mVpp)	50
Minimum Output Current (A)	4
Output Voltage (V)	30.5
Power Loss (W)	13.5
Rated Current (A)	4
Special Application	AS-Interface

Technical Attributes

Use In Crosslinking	Yes
---------------------	-----

Physical Attributes

Conformal Coating	No
-------------------	----

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	65W x 124H x 102D
-----------------	-------------------

Weight (g)	620
------------	-----

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	AS-Interface compliant, EU Declaration of Conformity, UL 508 Canada, UL 508 USA, UL 60950-1 Canada, UL 60950-1 USA, UK Declaration of Conformity
-------------------------	--