

## ABB E42N3ETG32W ACB E4.2N 3P 66KA WITHDRAWABLE 3200A EKIP TOUCH LSIG

E42N3ETG32W



### GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

### TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I <sub>cu</sub> (kA)	66
G (0.1 to 1 x I <sub>n</sub> ) - I <sub>4</sub> (A)	320-3200
I (1.5 to 15 x I <sub>n</sub> ) - I <sub>3</sub> (A)	4800-48000
L (0.4 to 1 x I <sub>n</sub> ) - I <sub>1</sub> (A)	1280-3200
No. of Poles	3P
Power Loss (W)	743
Rated Current (A)	3200
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	66
Rated Uninterrupted Current - I <sub>u</sub> (A)	3200
S (0.6 to 10 x I <sub>n</sub> ) - I <sub>2</sub> (A)	1920-32000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG

## DIMENSIONS

Frame Size	E4.2
------------	------

---

## PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

---

## RESOURCES

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

---