

Product No: SHT-1/2

ELKO DIGITAL TIME SWITCH 12-240VAC/DC 2C/O 16A D/W  
SHT-1/2

FEATURES

- Universal supply voltage: 12-240V AC/DC
- Daily, weekly program in one device
- Automatic conversion summer/winter time
- Switching: Program (AUTO)/constantly manually/ manually to next program change/ random (CUBE)
- Holiday program: Season selection option, when the device will not switch according to the standard program, but will be blocked
- Sealable cover, easy controlling via 4 buttons
- High accuracy due to special calibration
- Clear LCD display, minimum 1s interval
- Pulse/cyclic output



| General Information                |                            |
|------------------------------------|----------------------------|
| Brand                              | ELKO                       |
| Product Type                       | Time Switch                |
| Technical Attributes               |                            |
| Accuracy                           | ±1s/day                    |
| Battery Backup                     | 3 years                    |
| Channels                           | 2                          |
| Contacts                           | 2CO                        |
| Display Screen Type                | LCD                        |
| Function                           | Daily/weekly               |
| Power Consumption (W)              | 2                          |
| Rated Current (A)                  | 16                         |
| Timing Range                       | Programmable 24hrs, 7 days |
| Universal Supply Voltage AC/DC (V) | 12-240                     |
| Physical Attributes                |                            |
| Mounting Type                      | DIN Rail                   |



|                                    |            |
|------------------------------------|------------|
| Operational Temperature Range (°C) | -20 to +55 |
| Storage Temperature (°C)           | -30 to +70 |

| Protection & Standards  |                    |
|-------------------------|--------------------|
| Degree of Protection    | IP40 (Front Panel) |
| Pollution Degree        | 2                  |
| Standards and Approvals | EN 61812-1         |

| Resources                    |                                    |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | <a href="#">Download from here</a> |