



**Product:** [GECKO 8TX](#) 

8x FE TX, 12-24 V DC, -40-+60°C, Lite Managed

## Product Description

Lite Managed Industrial ETHERNET Rail-Switch, Ethernet/Fast-Ethernet Switch, Store and Forward Switching Mode, fanless design.

## Technical Specifications

### Product description

Type:	GECKO 8TX
Description:	Lite Managed Industrial ETHERNET Rail-Switch, Ethernet/Fast-Ethernet Switch, Store and Forward Switching Mode, fanless design.
Part Number:	942291001
Port type and quantity:	8 x 10BASE-T/100BASE-TX, TP-cable, RJ45-sockets, auto-crossing, auto-negotiation, auto-polarity

### More Interfaces

Power supply/signaling contact:	1 x plug-in terminal block, 3-pin
---------------------------------	-----------------------------------

### Network size - length of cable

Twisted pair (TP):	0-100 m
--------------------	---------

### Network size - cascability

Line - / star topology:	any
-------------------------	-----

### Power requirements

Operating Voltage:	18 V DC ... 32 V DC
Power consumption:	3.9 W
Power output in BTU (IT)/h:	13.3

### Software

Switching:	TOS/DSCP prioritization (Mapping TOS/DSCP to 802.1D/p), QoS (4 queues), Static unicast/multicast filter entries (up to 100), Flow Control, VLAN Support
Redundancy:	RSTP (IEEE 802.1D-2004), MRP Client
Management:	HTML5 Web-Interface, TFTP config file/firmware transfer, SNMP V1/V2/V3
Diagnostics:	Device status indication (LEDs), Log-File, RMON (1) statistics, Simple interface statistics, Topology Discovery according to IEEE 802.1AB (LLDP), Syslog
Configuration:	BOOTP/DHCP, HiDiscovery
Security:	SNMPv3 (authNoPriv), Possibility to disable each port, SSH, SSL
Time synchronisation:	SNTP Client
Industrial Profiles:	PROFINET Protocol

### Ambient conditions

MTBF (Telecordia SR-332 Issue 3) @ 25°C:	7 308 431 h
Air Pressure (Operation):	min. 700 hPa (+9842 ft; +3000 m)
Operating temperature:	-40-+60 °C
Storage/transport temperature:	-40-+85 °C
Relative humidity (non-condensing):	5-95 %

### Mechanical construction

Dimensions (WxHxD):	45,4 x 110 x 82 mm (w/o terminal block)
Weight:	223 g
Mounting:	DIN Rail
Protection class:	IP30

## Mechanical stability

IEC 60068-2-6 vibration:	3.5 mm, 5–8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4–150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock:	15 g, 11 ms duration

## EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field:	10 V/m (80 MHz - 1 GHz), 3 V/m (1,4 GHz – 6GHz)
EN 61000-4-4 fast transients (burst):	2 kV power line, 2 kV data line
EN 61000-4-5 surge voltage:	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz-80 MHz)

## EMC emitted immunity

EN 55032:	EN 55032 Class A
FCC CFR47 Part 15:	FCC 47CFR Part 15, Class A

## Approvals

Safety of industrial control equipment:	cUL 61010-1
---	-------------

## Reliability

Guarantee:	60 months (please refer to the terms of guarantee for detailed information)
------------	---

## Scope of delivery and accessories

Accessories to Order Separately:	Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC (CC), Mounting Accessories
Scope of delivery:	Device, 3-pin terminal block for the supply voltage and the grounding, Safety and general information sheet

## Further Instructions

Product Documentation:	<a href="https://www.doc.hirschmann.com">https://www.doc.hirschmann.com</a>
Certificates:	<a href="https://www.doc.hirschmann.com/certificates.html">https://www.doc.hirschmann.com/certificates.html</a>
Software Download:	<a href="https://hirschmann-support.belden.com/en-US/downloads">https://hirschmann-support.belden.com/en-US/downloads</a>

## History

Update and Revision:	Revision Number: 0.121 Revision Date: 01-02-2024
----------------------	--

## Variants

Item #	Type
942291001	GECKO 8TX

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.