

Product No: 101207743

SCHMERSAL KA-0808 CONNECTOR 101207743

FEATURES

- Pre-wired cable designed for use with a transmitter
- Features a 4-pole terminal connector with screw connection
- Includes 4 cable wires
- Cable length is 10 meters
- Rated operational DC voltage maximum of 250V
- IP67 rating, indicating dust tight and immersion up to 1m in water
- Operating temperature range from -30 °C to +90 °C
- Contact load capacity suitable for the Schmersal KA series safety light curtains



General Information

Brand	SCHMERSAL
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-06-01
eCl@ss Number, Version 9.0	27-27-26-01
ETIM 6.0	EC000030
ETIM 7.0	EC000030
Product Type	Accessory
Series	KA

Technical Attributes

Contact Material	Silver
Maximum Cable Cross Section (mm ²)	1.5
Maximum Fuse Rating	6 A gG D-fuse
Minimum Mechanical Life	20000000 Operations
No. of Poles	4
Rated Maximum Operational Voltage DC (V)	250
Switching Element	Opener (NC)
Terminal Type	Screw terminals

Utilisation Category DC-13

24 VDC

Physical Attributes

Enclosure Material	Grey cast iron, galvanised
Gross Weight (g)	195
Maximum Ambient Temperature (°C)	80
Maximum Temperature (°C)	90/80
Minimum Ambient Temperature (°C)	-30
Minimum Temperature (°C)	-30/-40
Net Weight (g)	164.539

Dimensions

Sensor Height (mm)	75
Sensor Length (mm)	149

Protection & Standards

Degree of Protection	IP67
Standards	EN IEC 60947-5-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------