

## Product No: S202MC50

### ABB S202MC50 MCB 10kA 2P 50A 400VAC C CURVE INDUSTRIAL

#### FEATURES

- - Protection against short circuit and thermal overload
- - Twin terminal for separate feeding of busbar and conductor
- - Contact Position Indication
- - Captive screws
- - Finger safety with IP20 terminals
- - Pole configuration 2P



#### General Information

Brand	ABB
Product Type	MCB
Series	S200M

#### Technical Attributes

Application	Commercial and Industrial
Breaking Capacity 400V AC - I <sub>cu</sub> (kA)	15
Curve Type	C Curve
Maximum Operational Voltage AC (V)	440
Maximum Operational Voltage DC (V)	125
Minimum Operational Voltage AC (V)	12
Minimum Operational Voltage DC (V)	12
No. of Poles	2P
Power Loss (W)	3.25/Pole
Rated Conditional Short-Circuit Current - I <sub>nc</sub> (kA)	25
Rated Current (A)	50
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	440

Rated Short-Circuit Capacity - I <sub>cn</sub> (kA)	10
Rated Voltage AC (V)	400

### Physical Attributes

Housing Material	Insulation Group II, RAL 7035
Mounting Type	DIN Rail

### Dimensions

Busbar Cross Section (mm <sup>2</sup> )	Top/Bottom - 10/10
Cable Cross Section - Flexible (mm <sup>2</sup> )	Top/Bottom - 25/25
Cable Cross Section - Solid/Stranded (mm <sup>2</sup> )	Top/Bottom - 35/35
Dimensions (mm)	85H x 69D x 35W
Pole Width (mm)	17.5

### Protection & Standards

Degree of Protection	IP20
Pollution Degree	3
Standards and Approvals	AS/NZS 60898-1,AS/NZS 60947-2,UL 1077

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------