

Product No: 3AXD5000034599

ABB ACQ580 30KW 62A IP21 WATER DRIVE W/ BLUETOOTH CP ACQ580-01-062A-4+J429

FEATURES

- ACQ580-01 drives offer innovative pump features for water and wastewater applications.
- The compact wall-mounted drive includes built-in pump functionalities like sensorless flow calculation and multipump control.
- Usability is enhanced with an intuitive control panel, PC tool Drive composer, and optional Bluetooth[®] control.
- The built-in energy calculator visualizes energy savings achieved with the drive.
- ACQ580-01 is available in IP21 enclosure for standard wall installation, with options for IP55 and flange mounting.



| General Information | |
|---------------------|----------------------|
| Brand | ABB |
| EAN | 6438177409854 |
| Product Type | Water and Wastewater |

| Technical Attributes | |
|-------------------------------|--|
| Application | Industrial, Commercial & Domestic |
| Communication Protocol | TCP/IP PROFIBUS CAN MODBUS DeviceNet / DeviceNet Safety PROFINET IO EtherNet/IP Other Bus Systems |
| Input Voltage AC (V) | 380 - 480 |
| Maximum Output Frequency (Hz) | 500 |
| Maximum Output Voltage AC (V) | 480 |
| No. of Analogue Inputs | 2 |
| No. of Analogue Outputs | 2 |
| No. of Digital Inputs | 6 |
| No. of Digital Outputs | 3 |



| Technical Attributes | |
|--|-----|
| Nominal Output Current (A) | 62 |
| Number of Other HW Interfaces | 2 |
| Number of Parallel Interfaces | 2 |
| Number of RS-485 Interfaces | 1 |
| Number of USB Interfaces | 1 |
| Output Power - Normal Duty (kW) | 30 |
| Relative Symmetric Net Frequency Tolerance | 5% |
| Relative Symmetric Net Voltage Tolerance | 10% |

Physical Attributes Contains

Control Element PC Connection

Dimensions

Dimensions (mm)

203W x 636H x 257D