

## Product No: HS6E-N44B03-G

### IDEC SAFETY SWITCH SPRING LOCK HS6E-N44B03-G

#### FEATURES

- Reversible mounting and angled cable allow four actuator insertion directions.
- Energy saving. 24V DC, 110 mA (solenoid: 100 mA, LED: 10 mA).
- Can be driven directly by a controller.
- Manual unlocking possible on three sides.
- LED indicator shows solenoid operation



#### General Information

Brand	IDEC
Product Type	Safety Interlock Switch

#### Technical Attributes

Minimum Electrical Life	100000
Minimum Mechanical Life	1000000
Rated Insulation Voltage (V)	300
Rated Thermal Current - Ith (A)	2.5
Resistance to Shock (m/s <sup>2</sup> )	100
Resistance to Vibrations	10 to 55

#### Physical Attributes

Operating Humidity	45 to 85%
Operational Temperature Range (°C)	-25 to 50

#### Dimensions

Cable Length (m)	3
Dimensions (mm)	15W × 75H × 75D
Weight (g)	410

#### Protection & Standards

Degree of Protection	IP67
----------------------	------

Pollution Degree	3
------------------	---

## Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------