

Product No: DVCII255-TT

DEHN DVCII255-TT SPD KIT T1+T2, 4P+PE In=25KA WITH C/O CONT.

FEATURES

- Includes 3 x DVCII255FM + DGPMI255FM + EB149
- Standards IEC/EN 61643-11



General Information

Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Follow Current Extinguishing Capability AC (kArms)	50 (L-N)
Integral Fuse	Yes
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25 (L-N)/100 (N-PE)
Maximum Continuous Operating Voltage MCOV AC (V)	255
No. of Poles	4P+PE
Nominal Discharge Current (8/20 μ s) - In (kA)	25 (L-N)
Nominal Voltage AC (V)	230
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Signal C/O Contact	Yes
Voltage Protection Level - Up (kV)	≤ 1.5

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

No. of Modules	8
----------------	---

Protection & Standards

Degree of Protection

IP20

Resources

Product catalogue (Flipbook)

[Download from here](#)