

Product No: BXTML4BE5

DEHN 4P CLASS1 5V 20kA 8/20US PLUG ONLY C/W LIFECHECK XTU BXTML4BE5

FEATURES

- Space-saving combined lightning current and surge arrester module
- With LifeCheck feature for protecting four single lines sharing a common reference potential as well as unbalanced interfaces
- LifeCheck can detect thermal or electrical overload, the arrester has to be replaced
- This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	920320
Suitable For	Pluggable DIN Rail Mounted

Technical Attributes

Earth Fault Protection	DIN rail (top hat rail)
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	10
Maximum Continuous Voltage AC (V)	4.2
Maximum Continuous Voltage DC (V)	6
Nominal Discharge Current (8/20 μ s) - In (kA)	20
Nominal Load Current AC - I _n (A)	1
Nominal Voltage DC (V)	5
Voltage Protection Level - Up (kV)	18

Dimensions

Dimensions (mm)	12W x 45H x 51D
Weight (g)	24
Weight (kg)	0.03

Protection & Standards

Degree of Protection

IP20

Resources

Product catalogue (Flipbook)

[Download from here](#)