

## Product No: 214065

## STAHL 8570/11-306-S019 WALL MOUNTING SOCKET 214065

## **FEATURES**

- Control devices for panel mounting
- Rated for 500 VAC continuous voltage
- Current capacity of 6 A
- Equipped with 2 Normally Open (NO) contacts
- Made from Polyamide material
- Operating temperature range from -20 °C to +60 °C
- Dual IP65 protection rating for both back and front
- Features include codable "latching," "spring return," and "key not removable" functions
- Part of the 8003 series by Stahl brand



| General Information |         |
|---------------------|---------|
| Brand               | STAHL   |
| Product Type        | Socket  |
| Series              | 8570/11 |

| Technical Attributes                             |     |
|--------------------------------------------------|-----|
| Maximum Continuous Operating Voltage MCOV AC (V) | 250 |
| Maximum Continuous Voltage AC (V)                | 250 |
| Maximum Operational Voltage AC (V)               | 250 |
| Minimum Operational Voltage AC (V)               | 200 |
| No. of Poles                                     | 3   |
| Nominal Output Current (A)                       | 16  |
| Output Current (A)                               | 16  |
| Rated Maximum Operational Voltage AC (V)         | 250 |
| Rated Minimum Operational Voltage AC (V)         | 200 |
| Rated Operational Current (A)                    | 16  |

| Physical Attributes            |            |
|--------------------------------|------------|
| Ambient Temperature Range (°C) | -30 to +55 |
| Colour                         | Blue       |



| Minimum Temperature (°C) | -30  |
|--------------------------|------|
| Mounting Type            | Wall |

Protection & Standards

Standards and Approvals

## Resources

Product catalogue (Flipbook)

Download from here

ATEX/IECeX