

Product No: DVM2TT2P255FM

**DEHN COMBINED ARRESTER TYPE 1+2+3 DEHNVENTIL M2 F.
SINGLE-PHASE TT A. TN SYSTEMS W. REMOTE SIGNAL.
CONTACT DVM2TT2P255FM**

FEATURES

- Two-pole, modular, pluggable combined arrester
- 2-module width
- With remote signalling contact
- Arrester as per EN 61643-11
- RAC spark gap technology
- Certified to VDE, KEMA and UL
- Energy coordination as per DIN CLC/TS 61643-12



General Information

Article No.	954115
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	50 (L+N-PE)
Maximum Continuous Operating Voltage MCOV AC (V)	255
No. of Poles	2P+PE
Nominal Discharge Current (8/20 μ s) - In (kA)	25/50
Nominal Voltage AC (V)	230
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Short-Circuit Withstand Capability - I _{sc} (kArms)	50 (L-N)
Signal C/O Contact	Yes
SPD Type	Type 1 + Type 2 + Type 3

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.09W x 0.12L x 0.05D
No. of Modules	2
Weight (kg)	0.32

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------