

Product No: FH204A25/0.03

ABB RCCB 4 POLE 25A TYPE A 6kA FH204A25/0.03

FEATURES

- Protection to people and installations against fault current to earth
- Protection against earth leakage faults
- Type A residual current
- Instantaneous operating characteristic



General Information

Brand	ABB
Product Type	RCCB

Technical Attributes

Leakage Current Type	A
No. of Poles	4
Power Loss (W)	1.3W per Pole
Rated Conditional Short-Circuit Current - Inc (kA)	6
Rated Current (A)	25
Rated Frequency (Hz)	50
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	500
Rated Operational Voltage AC (V)	230/400
Rated Residual Current (mA)	30
Rated Service Short-Circuit Breaking Capacity - Ics (kA)	1
Rated Voltage (V)	230/400
Type of Residual Current	A

Physical Attributes

Mounting Type	DIN Rail
No. of Modules - Width 17.5 mm	4
Operational Temperature Range (°C)	-5 to 40

Storage Temperature Range (°C)	-40 to 70
--------------------------------	-----------

Dimensions

Dimensions (mm)	70W x 85H x 69D
-----------------	-----------------

Weight (kg)	0.38
-------------	------

Protection & Standards

Degree of Protection	IP2X
----------------------	------

Standards and Approvals	IEC/EN 61008
-------------------------	--------------
