

## Product No: 274309

### STAHL 6036/1212-453-0151-11 LED TUBULAR LIGHT FITTING 274309

#### FEATURES

- LED tubular light fitting suitable for hazardous areas
- Compatible with 220 240 VAC or 209 240 VDC power sources
- Nominal power consumption of 48W
- Operating current rated at 0.250 A
- Features single-row LED technology with neutral white light output
- High luminous efficacy of 116 lm/W providing a total of 5575 lumens
- Equipped with a diffuser for even light distribution
- Wide operating temperature range from -55 °C to +60 °C, energize above -40 °C
- Robust IP66/IP67 ingress protection rating against dust and water

#### General Information

Brand	STAHL
Series	6036

#### Technical Attributes

Nominal Output Current (A)	0.7
Nominal Power (W)	13
Rated Maximum Operational Voltage AC (V)	48
Rated Maximum Operational Voltage DC (V)	48
Rated Minimum Operational Voltage AC (V)	24
Rated Minimum Operational Voltage DC (V)	24
Rated Operational Current (A)	0.7

#### Physical Attributes

Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40
Mounting Type	Surface



### Protection & Standards

Degree of Protection	IP66/67
Standards and Approvals	ATEX/IECEx

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------