

Product No:13048090335

**PFANNENBERG DTS 803IE 230V CSC 7035, 500W, IP54,230V
AC, 500W, IP54, 230 VAC 13048090335**

FEATURES

- Cooling unit with a cooling capacity of 800 W
- Operates on 230 VAC rated voltage, with a tolerance of $\pm 10\%$
- Features integrated condensate management system (*CM)
- Unimpeded airflow rates: 535 m³/h internal and 620 m³/h external
- Control temperature range from +25 °C to +45 °C
- Complies with IP54 protection rating against dust and water ingress
- Enclosure color RAL 7035
- Part of the DTS series by Pfannenberg
- Minimum operating AC voltage is 207V, maximum is 253V



General Information

| | |
|--------|-------------|
| Brand | PFANNENBERG |
| Series | DTS |

Technical Attributes

| | |
|--|---------------------|
| Cooling Capacity (W) | 500 |
| Cover | Steel powder coated |
| Current Consumption (A) | 1.7 |
| Noise Level (dBA) | ≤63 |
| Power Consumption (W) | 289 |
| Rated Frequency (Hz) | 50/60 |
| Rated Maximum Operational Voltage AC (V) | 253 |
| Rated Minimum Operational Voltage AC (V) | 207 |
| Rated Operational Power (kW) | 0.5 |
| Rated Voltage AC (V) | 230± 10% |
| Starting Current (A) | 3.5 |
| Terminal Type | Spring-type |

| | |
|------------------------------|-----|
| Unimpeded Airflow - External | 590 |
| Unimpeded Airflow - Internal | 275 |

Physical Attributes

| | |
|--------------------------------|------------------------|
| Ambient Temperature Range (°C) | +15 to +55 |
| Colour | RAL7035 |
| Housing Material | Galvanised sheet steel |
| Maximum Temperature (°C) | 55 |
| Minimum Temperature (°C) | 15 |
| Mounting Type | Door/Side |

Dimensions

| | |
|-----------------|--------------------|
| Dimensions (mm) | 325W X 670H X 200D |
|-----------------|--------------------|

Protection & Standards

| | |
|----------------------|------|
| Degree of Protection | IP54 |
|----------------------|------|

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|