

Product No: BXTML4BE12

DEHN BXTML4BE12 BLITZDUCTOR XT COMBINED ARRESTER T1, In=20KA

FEATURES

- - Space-saving
- - For protecting four single lines
- - LifeCheck SPD monitoring
- - Standards IEC/EN 61643-21



General Information

Article No.	920322
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	2.5 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	10.6
Maximum Continuous Operating Voltage MCOV DC (V)	15
Nominal Discharge Current (8/20 μ s) - In (kA)	10 (Per Line)
Nominal Voltage (V)	12
Total Discharge Current (10/350 μ s) - Itotal (kA)	10
Total Discharge Current (8/20 μ s) - Itotal (kA)	20
Voltage Protection Level - Up (kV)	≤ 0.050 (Line-Line)/ ≤ 0.037 (Line-PG)

Physical Attributes

Pluggable	Plugs into Base Part
-----------	----------------------

Dimensions

Module Width (mm)	12
-------------------	----

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)

[Download from here](#)
