

Product No: 210656

STAHL 9475/32-08-62 REMOTE I/O IS1+ DIGITAL OUTPUT MODULE FOR ZONE 1 EX I 210656

FEATURES

- Remote I/O IS1+ Digital output module for hazardous areas
- Suitable for Zone 1 Ex i environments
- Features 8 channels for Intrinsically Safe (I.S.) solenoid valves
- Each channel supports up to 30 mA current
- Ex i output rated operation at 12.6 V/30 mA
- Operating temperature range from -40 °C to +75 °C
- Allows module hot swapping in Zone 1 and Class I, Div. 1 locations
- Intrinsically Safe outputs with line fault monitoring capability
- Part of the 9475/32-08-XX series

General Information

Brand	STAHL
Series	9475/32-08-XX

Technical Attributes	
Communication Protocols	MODBUS
Maximum Nominal Output Voltage DC (V)	17.5
Nominal Output Current (A)	0.02
Nominal Power (W)	5.8

Physical Attributes	
Maximum Temperature (°C)	75
Minimum Temperature (°C)	-40
Mounting Type	DIN Rail

Protection & Standards	
Degree of Protection	IP20
Standards and Approvals	ATEX/IECeX



Resources

Product catalogue (Flipbook)

Download from here