

Product No: 943 940-999-003

**HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1130-CC
BBBBBBBBBBBBBBBBZZTT9999SMMHPH 943 940-999-003**

FEATURES

- Ruggedized Managed Rackmount Switch
- 8 x 10/100 Mbit/s RJ45 Ethernet ports
- 6 x 100BASE-FX, MM-LC fiber ports
- Operating temperature range from 0 °C to +60 °C
- Dual power supply input: 110/250 V DC and 110/230 V AC (plug-in connector)
- Layer 2 Professional network management features
- Approvals include cUL508, cUL1604 Class 1 Div2, Germanischer Lloyd, IEC 61850-3, IEEE 1613, EN 50121
- Designed for mounting in a standard 19" control cabinet
- IP Rating of IP30 for dust and ingress protection

General Information

Brand	HIRSCHMANN
Series	MAR1130

Technical Attributes

No. of 100Mb Ports	20
No. of 1GB Ports	2
No. of Ethernet Ports	2
No. of Fiber Ports	20
Rated Maximum Operational Voltage AC (V)	230
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

Physical Attributes

Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	19" Control Cabinet

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC 61850-3

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------