

Product No: IC225SSE102

EMERSON PACSAFE PLC ETH BASIC ST ANDALONE WITHOUT DISPLAY 10DIN 2DO REL, NONSAFE 4PNP IC225SSE102

FEATURES

- Same intuitive, icon-based programming with drag-and-drop configuration as the expandable models but in a compact footprint.
- Ten inputs, including four that can be used as non-safe outputs.
- Two six-amp safety relay outputs, each with three N.O. sets of contacts.
- Automatic Terminal Optimization (ATO) can increase the inputs from 10 to up to 14.
- Standard Industrial Ethernet two-way communication.
- External drive for fast swap and quick configuration without a PC.



General Information

Brand	EMERSON
Product Type	Controller

Benefits of Automation in Industrial Setting

- Reduced factory lead times
- Faster return on investment (ROI)
- Improved competitiveness in the market
- Consistent and enhanced part production and quality
- Smaller environmental footprint
- Improved planning capabilities
- Decreased reliance on outsourcing
- Optimal utilization of floor space

A programmable logic controller (PLC) is a highly capable solid-state control system that utilizes user-programmable memory to store instructions for executing various functions such as I/O control, logic operations, precise timing, accurate counting, three-mode (PID) control, communication protocols, arithmetic calculations, and data and file processing.

PLCs have evolved into sophisticated controllers capable of managing complex processes. Originally designed to perform the logic functions previously carried out by electrical hardware like relays, switches, and mechanical timers/counters. They find substantial application in SCADA systems and Distributed Control Systems and are often employed as the primary controller in smaller system configurations. PLCs play an extensive role in virtually all industrial processes, offering reliable and efficient control solutions.

In the realm of programmable logic controllers, below range of offerings feature renowned global brands including Emerson, and IDEC. Introducing VersaMax Modular I/O and Control - the epitome of versatility by Emerson. This exceptional control solution is compact, cost-effective, and adaptable, serving as a compact PLC, distributed I/O, or distributed control system. With its modular and scalable design, user-friendly features, and seamless integration with open systems, VersaMax proves to be a time and cost-saving solution for machine builders and end-users alike.

The IDEC MicroSmart FC6A series is available in two types, Plus and All-in-One. The Plus type features a dual RJ45 Ethernet port and embedded web server functions, and the All-in-One type

features an embedded serial port and RJ45 Ethernet port.

Discover the exceptional IDEC FT1A SmartAXIS controllers including the special FT1A with in-built touch screen HMI, meticulously crafted to offer unique features and advanced functions, perfect for applications with limited I/O needs. Benefit from its embedded Ethernet port, Modbus TCP and RTU support, USB for data logging and program updates, and Class I Div. 2 hazardous locations compliance.

Why Choose IPD for your industrial automation and PLC needs?

- 1. Comprehensive Product Range:** The collection features a comprehensive range of Industrial Automation and Programmable Controllers, to suit various applications and environments.
- 2. Quality Assurance:** At IPD, quality is paramount. We ensure that all the range of PLCs undergo rigorous testing and adhere to international standards. This commitment to quality guarantees optimal performance, reliability, and longevity.
- 3. Expertise and Support:** With our years of experience and in-depth knowledge, we understand the complexities of industrial automation. Our team of experts is ready to assist you in selecting the right PLC automation solution tailored to your specific requirements.

Order your programmable logic controllers from IPD and experience the transformative power of industrial automation. Browse below range of PLCs and take the first step towards streamlining your processes, increasing efficiency, and achieving unprecedented control. Contact us via 1300 556 601 to discuss your automation requirements and discover how we can be your trusted automation partner.

Technical Attributes

Input Current (mA)

Safety Input - Dual Channel (Dry Contact): 5-50 mA at 24 VDC, Safety Input - Dual Channel (Solid-

State): 50 mA at 15 – 30 VDC, Safety Input – Reset: 5–50 mA at 24 VDC

Input Operation	Simultaneous or Concurrent
No. of Inputs	Safe Inputs: 10, Convertible Inputs: 4
No. of Outputs	Independently Controlled Safe Outputs: 2, Non-Safe Output Configuration: Up to 4 PNP
Output Configuration	2 sets of 3 normally open
Rated Supply Voltage DC (V)	24
Terminal Type	Spring Clamp
Vibration	9–150 Hz at 1g occasional/0.5g continuous

Physical Attributes

Maximum Temperature (°C)	55
Relative Humidity	90% at 50°C

Dimensions

Dimensions (mm)	115 H x 45 W x 100 D
-----------------	----------------------

Protection & Standards

Degree of Protection	IP 20
Standards and Approvals	Category 4, PL e (EN ISO 13849), SIL CL 3 (IEC 62061, IEC 61508)

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------