

Product No: 943 940-999-014

**HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1030-CC
TTBBVVVVVVVVVVVVVVVVVVVVVVVVUGGHPH 943 940-999-014**

FEATURES

- Managed Rackmount Switch with ruggedized design
- 4 Ethernet Ports supporting 10/100/1000TX
- 24 Fiber Ports with 100BASE-FX, MM-LC connectors
- Operating temperature range from 0 °C to +60 °C
- Dual power supply inputs: 24/36/48 V DC (plug-in connector)
- Layer 2 Professional network management features
- IP Rating of IP30 for dust and ingress protection

General Information

Brand	HIRSCHMANN
Series	MAR1030

Technical Attributes

No. of 100Mb Ports	24
No. of 1GB Ports	2
No. of Ethernet Ports	2
No. of Fiber Ports	24
Rated Maximum Operational Voltage AC (V)	230
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

Physical Attributes

Maximum Temperature (°C)	85
Minimum Temperature (°C)	-40
Mounting Type	19" Control Cabinet

Protection & Standards

Degree of Protection

IP30

Standards and Approvals

IEC 61850-3

Resources

Product catalogue (Flipbook)

[Download from here](#)