

## Product No:101193048

### SCHMERSAL AZM 161SK-12/12RK-024-1637 SOLENOID INTERLOCK 101193048



#### General Information

Brand	SCHMERSAL
-------	-----------

#### Technical Attributes

No. of Auxiliary Contacts	2
Switching Frequency	1000/h
Contact Material	Gold-plated Silver (AgNi 15 + Au 0.3µm)
Holding Force (N)	2000
Latching Force (N)	30
Maximum Actuating Speed (m/s)	2
Maximum Cable Cross Section (mm <sup>2</sup> )	1 x 1.5
Maximum Fuse Rating	6 A gG D-fuse
Maximum Holding Force (N)	2600
Maximum Storage Temperature (°C)	85
Minimum Cable Cross Section (mm <sup>2</sup> )	1 x 0.25
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	20
Minimum Storage Temperature (°C)	-25
No. of Actuating Directions	3
No. of Safety Contacts	4
Positive Break Travel (mm)	10
Power Consumption (W)	10
Rated Control Voltage AC/DC (V)	24

Rated Insulation Voltage (V)	250
Rated Operational Current AC-15 (A)	Auxiliary Contacts - 4A, Safety Contacts - 4A
Rated Operational Current DC-13 (A)	Auxiliary Contacts - 2.5A, Safety Contacts - 2.5A
Rated Operational Voltage AC-15 (V)	230V AC
Rated Operational Voltage DC-13 (V)	24 VDC
Rated Short-circuit Current (A)	1000
Release Type	Manual
Switching Element	NO Contact, NC Contact
Switching Principle	Slow Action
Termination	Screw Terminals
Thermal Test Current (A)	6

### Physical Attributes

Cable Entry	4 x M16 x 1.5
Housing Material	Plastic, Glass-fibre Reinforced Thermoplastic, Self-extinguishing
Maximum Ambient Temperature (°C)	60
Minimum Ambient Temperature (°C)	-25

### Dimensions

Sensor Height (mm)	90
Sensor Length (mm)	30
Sensor Width (mm)	130

### Protection & Standards

Degree of Protection	IP67
Standards and Approvals	EN IEC 60947-5-1, EN ISO 13849-1

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------