

Product No: BXTML4BD12

DEHN BLITZDUCTOR XT COMBINED LIGHTNING CURRENT AND SURGE ARRESTER MOD BXTML4BD12

FEATURES

- Space-saving combined lightning current and surge arrester module
- LifeCheck feature for protecting two pairs of unearthed balanced interfaces
- LifeCheck detects thermal or electrical overload, indicates the arrester has to be replaced
- This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	920342
Suitable For	Pluggable DIN Rail Mounted

Technical Attributes

Earth Fault Protection	DIN rail (top hat rail)
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	10
Limiting Frequency (MHz)	2.8
Maximum Continuous Operating Voltage MCOV AC (V)	10.6
Maximum Continuous Operating Voltage MCOV DC (V)	15
Maximum Continuous Voltage AC (V)	10.6
Maximum Continuous Voltage DC (V)	15
Nominal Discharge Current (8/20 μ s) - In (kA)	20
Nominal Load Current AC - I _n (A)	1
Nominal Voltage (V)	12
Nominal Voltage DC (V)	12
SPD Type	1
Voltage Protection Level - Up (V)	line-line for Iimp D1 (UP) \leq 26 V line-PG for Iimp D1 (UP) \leq 550 V

line-line at 1 kV/ μ s C3 (UP) \leq 19 V
line-PG at 1 kV/ μ s C3 (UP) \leq 550 V

Voltage Protection Level - Up (kV)

19

Physical Attributes

Colour

Yellow

Enclosure Material

Polyamide PA 6.6

Mounting Type

On Basic Element

Operational Temperature Range (°C)

-40 to 80

Dimensions

Dimensions (mm)

12W x 45H x 51D

Weight (kg)

0.023

Protection & Standards

Degree of Protection

IP20

Standards and Approvals

IEC 61643-21 / EN 61643-21

Resources

Product catalogue (Flipbook)

[Download from here](#)