

Product No: PPI0A2-50

NOVARIS SURGE FILTER, 230VAC, 50KA MAX DISCHARGE PPI0A2-50

FEATURES

- - All mode protection
- - MOV/LC filter/MOV protection stages
- - LED power and status



General Information

Brand	NOVARIS
Product Type	Surge Filter
Series	PPI0

Technical Attributes

Connection Type	Series
Maximum Continuous Operating Voltage MCOV AC (V)	275 (L-N, N-PE)
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	50
No. of Outlets	2
No. of Phases	1
Nominal Discharge Current (8/20 μ s) - I _n (kA)	20
Nominal Voltage AC (V)	230
Rated Load Current - I _n (A)	10
Voltage Protection Level (3kA 8/20 μ s) - U _p (kV)	<0.6 (L-N)
Voltage Protection Level - U _p (kV)	<0.8 (L-N)

Physical Attributes

Mounting Type	Free standing
Operational Temperature Range (°C)	-40 to 70

Dimensions

Dimensions (mm)	60H x 137L
-----------------	------------

Weight (kg) 1.3

Protection & Standards

Degree of Protection IP20

Standards and Approvals IEC 61643-11, AS/NZS 1768, IEEE C62.41, IEC 1000-4-5

Resources

Product catalogue (Flipbook) [Download from here](#)

TECHNICAL DRAWING

