

ELKO POWER RELAY MODULE 1C/O 16A 230V AC VS316/230

VS316/230

FEATURES

- High intensity LED
- DIN Rail mountable, 1 DIN module wide
- Degree of protection: Front panel
- Maximum time of changeover of contacts is 10ms



GENERAL INFORMATION

Brand	ELKO
Product Type	Power Relay

TECHNICAL ATTRIBUTES

Contact Material	Silver alloy
Contacts	3CO (TPDT)
Function	Switching single/triple phase load
No. of Phases	3
Overvoltage Category	3
Rated Current (A)	16
Rated Frequency (Hz)	50/60
Time Ranges	50ms
Universal Supply Voltage AC (V)	230

PHYSICAL ATTRIBUTES

LED Colour	Output: Red
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-20 to +55
Storage Temperature (°C)	-30 to +70

DIMENSIONS

Dimensions (mm)	90 x 17.6 x 64
No. of Modules	1

PROTECTION & STANDARDS

Degree of Protection	IP40 (Front Panel), IP20 (Terminals)
Pollution Degree	2
Standards and Approvals	EN 60669-1, EN60669-2-1, EN60715

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------