

Product No: 101059300

SCHMERSAL TL 422-01Y-RMS POSITION SWITCH 101059300



General Information

Brand	SCHMERSAL
-------	-----------

Technical Attributes

Actuating Angle	30° - From Left of Switch Axis, 30° - From Right of Switch Axis
Actuating Element	Roller Lever
Contact Material	Silver
Maximum Actuating Speed (m/s)	3
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	16 A gG D-fuse
Minimum Actuating Speed (mm/min)	1
Minimum Cable Cross Section (mm ²)	1.5
Minimum Mechanical Life	10000000 Operations
No. of Normally-closed Contacts	1
Rated Insulation Voltage (V)	400
Rated Operational Current AC-15 (A)	4
Rated Operational Voltage AC-15 (V)	400V AC
Switching Element	Opener (NC)
Switching Principle	Slow Action
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	16
Utilisation Category	AC-15

Physical Attributes

Castor Material	Plastic
Contact Opening (mm)	2 x 6
Enclosure Coating Material	Painted
Housing Material	Grey Cast Iron, Galvanised
Maximum Ambient Temperature (°C)	90
Minimum Ambient Temperature (°C)	-30

Dimensions

Castor Diameter (mm)	36
Castor Width (mm)	9
Sensor Height (mm)	164
Sensor Length (mm)	63
Sensor Width (mm)	106

Protection & Standards

Degree of Protection	IP65
Standards and Approvals	EN IEC 60947-5-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------