

Product No: UPS303HH33N035

DELTA HPH 30 KVA/30 KW GEN 2 MONOBLOCK NO INTERNAL BATTERIES UPS303HH33N035

FEATURES

- Delta HPH 30KVA/30KW Gen 2 Monoblock
- No Internal Batteries,
- Requires 80 x 12V 9Ah Batteries (Not Included)
- SMART Slot x 1, MINI Slot x 1
- 490W x 830D x 1400H (mm) - 162kg

General Information

Brand	DELTA
Product Type	Accessory
Series	HPH

Technical Attributes

Battery Charge Current (A)	15 (Max inbuilt)
Battery Charge Voltage DC (V)	±272 (adjustable from 204 V to 312 V)
Battery Nominal Voltage DC (V)	±240 (default, ±180 ±276 configurable)
Communication Interface	External battery temperature detection x1, Output dry contact x4, Input dry contact x2, Parallel port x2, USB Port x1, RS232 Port x1, REPO Port x1, Mini Slot x2
Input Frequency Range (Hz)	40-70
Noise Level (dBA)	< 56
Nominal Voltage AC (V)	220/380, 230/400, 240/415
Output Voltage AC (V)	220/380, 230/400, 240/415 (3-phase, 4-wire + G)
Voltage Range AC (V)	305-478 (full load), 228-478 (70% load)

Physical Attributes

Humidity	0-95% (non-condensing)
Operational Temperature Range (°C)	0-40°
Power Rating (W)	30kVA

Dimensions

Dimensions (mm)	240 W x 630 D x 650 H
-----------------	-----------------------

Weight (kg)	50
-------------	----

Protection & Standards

Degree of Protection	IP20 (Standard), IP42 (Optional for long backup model)
----------------------	--

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------