

## ABB S804NC10 HIGH PERF. MCB 36kA 4P 10A 415VAC C CURVE

S804NC10

### FEATURES

- Protection against short circuit and thermal overload
- Interchangeable terminal, failsafe cage or ring lug terminal
- Laser printed data for quick identification
- Contact position indication
- Finger safety with IP20 terminals
- Pole configuration 4P



### GENERAL INFORMATION

Brand	ABB
Product Type	MCB
Series	S800N

### TECHNICAL ATTRIBUTES

Application	Commercial and Industrial
Breaking Capacity 400V AC - Icu (kA)	36
Curve Type	C Curve
Maximum Operational Voltage AC (V)	690
Maximum Operational Voltage DC (V)	500
Minimum Operational Voltage AC (V)	12
No. of Poles	4P
Power Loss (W)	1.5/Pole
Rated Conditional Short-Circuit Current - Inc (kA)	36
Rated Current (A)	10
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	690
Rated Operational Voltage AC (V)	400/690
Rated Operational Voltage DC (V)	500
Rated Short-Circuit Capacity - Icn (kA)	30
Rated Voltage AC (V)	400

**PHYSICAL ATTRIBUTES**

Housing Material	Insulation group I, RAL 7035
Mounting Type	DIN Rail

**DIMENSIONS**

Cable Cross Section - Flexible (mm <sup>2</sup> )	Top/Bottom - 70/70
Cable Cross Section - Solid/Stranded (mm <sup>2</sup> )	Top/Bottom - 50/50
Dimensions (mm)	95H x 82.5D x 106W
Pole Width (mm)	27

**PROTECTION & STANDARDS**

Degree of Protection	IP20
Pollution Degree	3
Standards and Approvals	AS/NZS 60898-1,AS/NZS 60947-2

**RESOURCES**

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------