

PRODUCT-DETAILS

CAL16-11D

CAL16-11D Auxiliary Contact Block



General Information

Extended Product Type	CAL16-11D
Product ID	SK829002-D
EAN	7320500029695
Catalog Description	CAL16-11D Auxiliary Contact Block
Long Description	2 pole screw type right outer side mounted auxilliary contact block, instantaneous N.O. and N.C. contacts, suitable for standard industrial environments

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010
Product Main Type	CAL16

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202
Instructions and Manuals	5309660-30
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	12.5 mm
Product Net Depth / Length	70 mm
Product Net Height	68 mm
Product Net Weight	0.05 kg

Technical

Connecting Terminals (delivered in open position)	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Minimum Switching Capacity	0.25 VA/ 12 V / 5 mA
Power Loss	at Rated Operating Conditions per Pole 0.2 W
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I_{θ})	(500 V) 1 A (690 V) 1 A (24 / 127 V) 6 A (220 / 240 V) 6 A (380 / 400 V) 4 A
Rated Operational Current DC-13 (I_{θ})	(24 V) 6 A (48 V) 6 A (72 V) 4 A (125 V) 1.8 A (250 V) 0.6 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 100 A for 1 s 50 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Suitable For	EH175 EH210 EH260 EH300 EH370 EH450 EH550 EH700 EH800 EH1200 EHDB220 EHDB280 EHDB360 EHDB520 EHDB650 EHDB800 EHDB960 EK110 EK150 EK175 EK210 EK370 EK550 EK1000

Suitable for Product Class

Block Contactors

Technical Information

AUXILIARY CONTACT

Environmental

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-5-1, Θ = 40 °C 16 A
Degree of Protection	IP20
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CQC Certificate	CQC2012010304553193
Declaration of Conformity - CCC	2020980304001516
Declaration of Conformity - CE	2CMT2015-005448
Declaration of Conformity - UKCA	2CMT2020-006119

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Height	18 mm
Package Level 1 Gross Weight	0.06 kg
Package Level 1 EAN	7320500029695

Classifications

eClass	V11.1 : 27371302
E-Number (Finland)	3846772
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
Object Classification Code	K

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

