

## **Product No: OT2500E04CP**

## ABB OT2500E04CP CHANGE-OVER SWITCH OT2500E04CP

## **FEATURES**

- High current capacity, making it suitable for applications with high electrical demands
- Robust and secure handle design featuring padlockable positions for added safety
- Fourth pole positioned on the right side for switched simultaneous function
- Convenient front operation



General Information	
Brand	ABB
Product Type	Manual
Suitable For	Distribution Board Installation
Туре	Main Switch

Technical Attributes	
Conventional Free-Air Thermal Current - Ith (A)	2500
Indication	I-O-II
Maximum Operational Voltage AC (V)	1000
Mode of Operation	Front
No. of Poles	4
No. of Switches	1
Padlockable	Padlockable in O-position
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss (W)	85
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-22A 415V (A)	2500
Rated Operational Voltage (V)	1000
Rated Operational Voltage AC (V)	415
Rated Short-Time Withstand Current - Icw (kA)	55
Terminal Type	Bolt
Transition Type	Open



Physical Attributes	
Control Element Colour	Black
Handle Type	Pistol
Included	Handle, Shaft
Interlockable	Yes
Mounting Type	Front Mount 4-hole

Dimensions	
Dimensions (mm)	664W x 377H x 335D
Weight (kg)	86

Protection & Standards	
Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>