

Product No: VS116U

ELKO POWER RELAY MODULE 1C/O 8A 12-240VAC/DC VS116U

FEATURES

- - High intensity LED
- - DIN Rail mountable, 1 DIN module wide
- - Degree of protection: Front panel - IP40
- - Maximum time of changeover of contacts is 10ms



General Information

Brand	ELKO
Product Type	Power Relay

Technical Attributes

Contact Material	Silver alloy
Contacts	1CO (SPDT)
Function	Switching single phase load
No. of Phases	1
Overtoltage Category	3
Power Loss (W)	1.7
Rated Current (A)	16
Rated Frequency (Hz)	50/60
Time Ranges	2s
Universal Supply Voltage AC/DC (V)	12-240

Physical Attributes

LED Colour	Output: Red
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-20 to +55
Storage Temperature (°C)	-30 to +70

Dimensions

Dimensions (mm)	90 x 17.6 x 64
-----------------	----------------

No. of Modules	1
----------------	---

Protection & Standards

Degree of Protection	IP40 (Front Panel), IP20 (Terminals)
----------------------	--------------------------------------

Pollution Degree	2
------------------	---

Standards and Approvals	EN 60669-1, EN60669-2-1, EN60715
-------------------------	----------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------