

## **Product No: CM-MSS.22S**

## ABB THERMISTOR MOTOR PROTECTION RELAY 2C/O 24VAC/DC CM-MSS.22S

## **FEATURES**

- - Continuous Operation
- - Reliable in harsh conditions
- - Easy Installation
- - Direct Temperature Monitoring
- - Motor protection using protective devices
- - Short circuit detection
- - ATEX certification



General Information	
Brand	ABB
Product Type	Motor Protection Relay
Reference No.	1SVR730700R0200

Technical Attributes	
Connection Type	Double-chamber cage connection terminals
Contacts	2CO (SPDT)
Duty Time	100%
No. of LED	3
Overvoltage Category	III
Rated Control Supply Voltage AC/DC (V)	24
Rated Current (A)	4
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Sensor Type	PTC Type A
Terminal Type	Screw

Physical Attributes	
LED Colour	U: Green, F: Red, R: Yellow
Mounting Type	DIN Rail



Storage Temperature (°C)

-40 to +85

Dimensions	
Dimensions (mm)	97W x 109H x 30D
Weight (kg)	0.132

Protection & Standards	
Degree of Protection	IP50 (Housing), IP20 (Terminals)
Pollution Degree	3
Standards and Approvals	CAN/CSA C22.2 No.14, EN 50495, IEC/EN 63000, IEC/EN 60079-7, IEC/EN 60947-5-1, IEC/EN 60947-8, UL 508

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>