

Product No: MS132-16

ABB MS132-16 MANUAL MOTOR STARTER 10 ... 16 A MS132-16

FEATURES

- Compact design, ideal for installations with limited space
- Provides reliable protection against short-circuits, overload and phase failures
- High breaking capacity
- Features a lockable rotary handle with clear switch position indication
- Suitable for both 3 phase and single phase applications



General Information	
Brand	ABB
Product Type	Manual Motor Starter

Technical Attributes	
Design of Control Element	Turn Button
Breaking Capacity 400V AC - Icu (kA)	100
Main Circuit Electrical Connection	Screw Connection
No. of Poles	3
Overload Release Current Setting (A)	10
Phase Failure Sensitive	Yes
Power Loss (W)	8.4
Rated Instantaneous Short-Circuit Current - Ii (A)	240
Rated Insulation Voltage (V)	690
Rated Operational Current (A)	16
Rated Operational Power AC-3 400V (kW)	7.5
Rated Operational Voltage (V)	250
Rated Uninterrupted Current - Iu (A)	16
Switching Type	Thermomagnetic
Terminal Type	Screw Terminals
Thermal Current Setting Range (A)	10.0 - 16.0



Thermal Overload Protection	Yes	
Dimensions		
Dimensions (mm)	45W x 97.8H x 86.55D	
Protection & Standards		
Degree of Protection	IP20	
Resources		

Download from here

Product catalogue (Flipbook)

1300 556 601 | ipd.com.au | 19-02-2024