

IEC LV MOTORS

Motor data sheet

M3BP 355SMA 4

Definition	Data	Unit	Remarks
Product code	3GBP352210-***K		CalcId: 3GZF021035-88
Voltage code	D		
Type/Frame	M3BP 355SMA 4		
Design	CENELEC		
Efficiency class	IE3		IEC 60034-2-1:2014
Rated output P_N	200	kW	
Rated voltage U_N	415	V	± 5 % (IEC 60034-1)
Rated frequency f_N	50	Hz	± 2 % (IEC 60034-1)
Rated speed n_N	1491	r/min	
Rated current I_N	337	A	
Starting current I_S/I_N	7.7		
Nominal torque T_N	1280	Nm	
Locked rotor torque T_l/T_N	2.3		
Maximum torque T_b/T_N	2.9		
Efficiency - full load 100%	96.0	%	IEC 60034-2-1:2014
Efficiency - 75%	96.0	%	
Efficiency - 50%	95.4	%	
Power factor - full load 100%	0.86		
Bearing DE/NDE	6322/C3 6316/C3		
Sound pressure level L_{pA} dB	74	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm ²	5.9	kg-m ²	
Weight	1610	kg	
Ambient temperature	40	°C	
Motor losses at VSD operating points	losses in efficiency %	losses in Watt	losses in relative to nom. power %
VSD Speed 90% Torque 100%	95.6	8284	4.1
VSD Speed 50% Torque 100%	94.1	6270	3.1
VSD Speed 25% Torque 100%	90.1	5494	2.7
VSD Speed 90% Torque 50%	94.7	5037	2.5
VSD Speed 50% Torque 50%	94.0	3192	1.6
VSD Speed 50% Torque 25%	91.5	2322	1.2
VSD Speed 25% Torque 25%	87.9	1721	0.9