

## ABB CHANGEOVER SWITCH KIT 80A 3P-3P DIN MOUNT OT80F3CK-K

OT80F3CK-K



Brand ABB  Product Type Manual  TECHNICAL ATTRIBUTES Conventional Thermal Current - Ithe (A) 80 No. of Poles 3P- 3P Padlockable Non-padalockable Power Loss (W) 4.5 Rated Operational Current AC-22A 415V (A) 80 Rated Operational Current AC-22A 415V (A) 80 Rated Operational Current AC-23A 415V (A) 75 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Current AC-3A 500V (A) 58 Rated Operational Voltage AC/DC (V) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS  Degree of Protection IP20 (Front)		
Product Type Manual  TECHNICAL ATTRIBUTES Conventional Thermal Current - Ithe (A) 80 No. of Poles 3P - 3P Padlockable Non-padalockable Power Loss (W) 4.5 Rated Operational Current AC-22A 415V (A) 80 Rated Operational Current AC-22A 500V (A) 80 Rated Operational Current AC-23A 415V (A) 75 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Current AC-23A 500V (A) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	GENERAL INFORMATION	
TECHNICAL ATTRIBUTES  Conventional Thermal Current - Ithe (A) 80  No. of Poles 3P - 3P  Padlockable Non-padalockable  Power Loss (W) 4.5  Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Voltage AC/DC (V) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black  Handle Type Knob  Mounting Type DIN	Brand	ABB
Conventional Thermal Current - Ithe (A) 80  No. of Poles 3P- 3P  Padlockable Non-padalockable  Power Loss (W) 4.5  Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Voltage AC/DC (V) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black  Handle Type Knob  Mounting Type DIN	Product Type	Manual
Conventional Thermal Current - Ithe (A) 80  No. of Poles 3P- 3P  Padlockable Non-padalockable  Power Loss (W) 4.5  Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Voltage AC/DC (V) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black  Handle Type Knob  Mounting Type DIN		
No. of Poles Padlockable Non-padalockable Non-padalockable Power Loss (W) 4.5 Rated Operational Current AC-22A 415V (A) Rated Operational Current AC-22A 500V (A) Rated Operational Current AC-23A 415V (A) Rated Operational Current AC-23A 500V (A) Rated Operational Current AC-23A 500V (A) Rated Operational Current AC-23A 500V (A) Rated Operational Voltage AC/DC (V) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	TECHNICAL ATTRIBUTES	
Padlockable Non-padalockable  Power Loss (W) 4.5  Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Current AC-23A 500V (A) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	Conventional Thermal Current - Ithe (A)	80
Power Loss (W) 4.5  Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Voltage AC/DC (V) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	No. of Poles	3P - 3P
Rated Operational Current AC-22A 415V (A) 80  Rated Operational Current AC-22A 500V (A) 80  Rated Operational Current AC-23A 415V (A) 75  Rated Operational Current AC-23A 500V (A) 58  Rated Operational Voltage AC/DC (V) 750  Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	Padlockable	Non-padalockable
Rated Operational Current AC-22A 500V (A) 80 Rated Operational Current AC-23A 415V (A) 75 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Voltage AC/DC (V) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	Power Loss (W)	4.5
Rated Operational Current AC-23A 415V (A) 75 Rated Operational Current AC-23A 500V (A) 58 Rated Operational Voltage AC/DC (V) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	Rated Operational Current AC-22A 415V (A)	80
Rated Operational Current AC-23A 500V (A) 58 Rated Operational Voltage AC/DC (V) 750 Transition Type Open  PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	Rated Operational Current AC-22A 500V (A)	80
Rated Operational Voltage AC/DC (V)  Transition Type  PHYSICAL ATTRIBUTES  Handle Colour  Handle Type  Mounting Type  PROTECTION & STANDARDS  750  Open  Black  Knob  DIN	Rated Operational Current AC-23A 415V (A)	75
Transition Type Open  PHYSICAL ATTRIBUTES  Handle Colour Black  Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	Rated Operational Current AC-23A 500V (A)	58
PHYSICAL ATTRIBUTES Handle Colour Black Handle Type Knob Mounting Type DIN  PROTECTION & STANDARDS	Rated Operational Voltage AC/DC (V)	750
Handle Colour Black Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	Transition Type	Open
Handle Colour Black Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS		
Handle Type Knob  Mounting Type DIN  PROTECTION & STANDARDS	PHYSICAL ATTRIBUTES	
Mounting Type DIN  PROTECTION & STANDARDS	Handle Colour	Black
PROTECTION & STANDARDS	Handle Type	Knob
	Mounting Type	DIN
Degree of Protection IP20 (Front)	PROTECTION & STANDARDS	
	Degree of Protection	IP20 (Front)