

Product No: BCOMODML2BD12

DEHN PROTECTION MODULE FOR 1 PAIR BLITZDUCTORCONNECT W. FAULT INDICATION BCOMODML2BD12

FEATURES

- Pluggable combined arrester module
- Tested to EN/IEC 61643-21
- Energy coordinated according to IEC 61643-22
- Width of 6 mm
- Replacement module



General Information

| | |
|--------------|-----------------------|
| Article No. | 927042 |
| Brand | DEHN |
| Product Type | Signal Line Protector |

Technical Attributes

| | |
|--|--|
| Lightning Impulse Current (10/350 μ s) - Iimp (kA) | 1.5 (Per Line) |
| Maximum Continuous Operating Voltage MCOV AC (V) | 10.6 |
| Maximum Continuous Operating Voltage MCOV DC (V) | 15 |
| Maximum Discharge Current (8/20 μ s) - I _{max} (kA) | 20 |
| Nominal Discharge Current (8/20 μ s) - I _n (kA) | 5 (Per Line) |
| Nominal Voltage (V) | 12 |
| Operating State/Fault Indication | Green/Red |
| Total Discharge Current (10/350 μ s) - I _{total} (kA) | 3 |
| Total Discharge Current (8/20 μ s) - I _{total} (kA) | 10 |
| Voltage Protection Level - U _p (kV) | ≤ 0.032 (Line-Line)/ ≤ 0.6 (Line-PG) |

Physical Attributes

| | |
|-----------|---------------------------|
| Pluggable | Plugs in to BCO Base Part |
|-----------|---------------------------|

Dimensions

| | |
|-----------------|-----------------------|
| Dimensions (mm) | 0.08W x 0.12L x 0.01D |
|-----------------|-----------------------|

| | |
|-------------------|---|
| Module Width (mm) | 6 |
|-------------------|---|

| | |
|-------------|------|
| Weight (kg) | 0.04 |
|-------------|------|

Protection & Standards

| | |
|----------------------|------|
| Degree of Protection | IP20 |
|----------------------|------|

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|