

Product No: 151156127

SCHMERSAL POSITION SWITCH, 2 SAFETY CONTACTS 151156127



General Information

Brand	SCHMERSAL
Product Type	Limit Switch

Technical Attributes

Safety Functions	Yes
Switching Frequency	5000/h
Switchover Time (ms)	5.5ms (Maximum)
Actuating Element	Plunger
Contact Material	Silver
Maximum Actuating Speed (m/s)	1
Maximum Bounce Duration (ms)	3
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	6 A gG D-fuse
Minimum Actuating Force (N)	9
Minimum Actuating Speed (mm/min)	10
Minimum Cable Cross Section (mm ²)	0.75
Minimum Mechanical Life	20000000 Operations
Minimum Positive Break Force (N)	19
No. of Safety Contacts	2
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Current AC-15 (A)	4

Rated Operational Current DC-13 (A)	1
Rated Operational Voltage AC-15 (V)	230V AC
Rated Operational Voltage DC-13 (V)	24V DC
Rated Short-circuit Current (A)	1000
Switching Element	Opener (NC)
Switching Principle	Snap Action
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	10
Utilisation Category	DC-13

Physical Attributes

Housing Material	Plastic, Glass-fibre-reinforced
Maximum Ambient Temperature (°C)	80
Minimum Ambient Temperature (°C)	-30

Dimensions

Sensor Height (mm)	73.5
Sensor Length (mm)	30
Sensor Width (mm)	30

Protection & Standards

Degree of Protection	IP67
Standards	EN ISO 13849-1
Standards and Approvals	EN IEC 60947-5-1, EN ISO 13849-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------