

Product No:101157376

SCHMERSAL SAFETY SWITCH, 1 SAFETY CONTACT 101157376

Note: Individual coding available on request



General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	High
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-26-01
eCl@ss Number, Version 9.0	27-44-01-02
ETIM 6.0	EC000221
ETIM 7.0	EC002544
Housing Construction Form	Norm construction design
Product Type	Safety Switch
Working Principle	Electromechanical

Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver
Maximum Actuating Speed (m/s)	2
Maximum Cable Cross Section (mm ²)	2 x 2.5
Maximum Fuse Rating	6 A (slow blow)
Minimum Cable Cross Section (mm ²)	0.34
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	20
No. of Safety Contacts	2

Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	250
Rated Short-circuit Current (A)	1000
Switching Element	NC contact, NO contact
Switching Principle	Slow action
Terminal Type	Screw terminals M20 x 1.5
Thermal Test Current (A)	0.25
Utilisation Category	DC-13 AC-15
Utilisation Category DC-13	0.05 A

Physical Attributes

Actuator Type	Plunger
Enclosure Material	Aluminium
Gross Weight (g)	450
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	-30
Net Weight (g)	45
Storage Temperature (°C)	-40 to 85
Wire Cross-Section	13 AWG

Dimensions

Sensor Height (mm)	27
Sensor Length (mm)	33

Protection & Standards

Degree of Protection	IP30
Standards	EN IEC 61496-1 / EN IEC 61496-2

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------