

Product No:238147

STAHL 6009/522-9617-1622-71 EMERGENCY LUMINAIRE FOR
FLUORESCENT LAMPS GRP 238147

FEATURES



- LED indicator lamp suitable for hazardous areas
- Mounting type: Dinrail mounting for easy installation
- Voltage range: 10.80 30.00 VAC or DC, versatile power compatibility
- Light color: White LED for clear visibility
- Enclosure material: Polyamide for durability
- Temperature range: Operable from -30 °C to +60 °C, suitable for extreme conditions
- Protection class: IP20 rating indicating protection against solid objects larger than 12mm but not water
- Certification: ATEX/IECEx certified for safety in explosive atmospheres

General Information	
Brand	STAHL
Product Type	Emergency
Series	6009/5
Technical Attributes	
Application	Application range (zones) - 1, 2, 21, 22
Battery Size	6V, 7.0Ah
Lamp Base	G13 lamp base
Lamp Wattage (W)	18
No. of Lamps	2
Nominal Power (W)	18
Rated Frequency (Hz)	50 - 60
Rated Maximum Operational Voltage AC (V)	240
Rated Minimum Operational Voltage AC (V)	220
Rated Operational Voltage AC (V)	220 - 240



Physical Attributes

Ambient Temperature Range (°C)	-30 to +55
Cable Type	Finely stranded, solid
Colour	Enclosure - Light Grey (RAL 7035)
Enclosure Material	Polyester resin, Glass fibre reinforced
Lamp Type	LED
Maximum Temperature (°C)	50
Minimum Temperature (°C)	-30
Mounting Type	Surface

Dimensions

Cable Cross Section (mm²)	4 - 6
Dimensions (mm)	183.5W x 125H x 857D

Protection & Standards

Certifications	IECEX, ATEX
Degree of Protection	IP66/67
Rated Impact Resistance	IK10
Standards and Approvals	ATEX/IECeX

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------