

Product No:101172765

SCHMERSAL SEPG05.3.4.0.22/95 TWO-HAND CONTROL PANEL 101172765

FEATURES

- Two-hand control panel with aluminium enclosure
- Construction kit configuration available
- Designed for use with EMERGENCY-OFF applications
- Equipped with 1 Emergency Stop button (40 mm diameter)
- Includes 2 openers and 2 shutters
- Features 2 operating push buttons (40 mm diameter)
- Screw connection terminal connector
- Thermal test current rated at 10 A
- Utilisation category AC-15: Rated for 250 VAC, 8 A



General Information

Brand	SCHMERSAL
Recommended Product Combination	SRB201ZH
Series	SEP

Technical Attributes

Maximum Cable Cross Section (mm ²)	1.5
Minimum Mechanical Life	10000000 Operations
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	2
Rated Insulation Voltage (V)	440
Rated Operational Current AC-15 (A)	8
Rated Operational Current DC-13 (A)	5
Rated Operational Voltage AC-15 (V)	250V AC
Rated Operational Voltage DC-13 (V)	24V DC
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	10
Utilisation Category	DC-13

Physical Attributes

Enclosure Coating Material	Powder-coated
----------------------------	---------------

Housing Material	Aluminium
------------------	-----------

Dimensions

Depth (mm)	160
------------	-----

Height (mm)	184
-------------	-----

Width (mm)	494
------------	-----

Protection & Standards

Degree of Protection	IP65
----------------------	------

Standards and Approvals	EN IEC 60947-5-1
-------------------------	------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------