

## Product No: MSB604020G

## IDE IDE66 ROLLED MILD STEEL SINGLE DOOR WALL MOUNTED ENCLOSURE 600Hx400Wx200Dmm GREY MSB604020G

## FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- - Primer coated and hardened RAL 7035 polyester paint, embossed, with UV protection
- - Substitute G with A for orange colour RAL 2008
- - Mounting plate included



| General Information   |  |
|-----------------------|--|
| Brand                 | IDE  |
| Customs Tariff Number | 85.38.10.00  |
| EAN                   | 8431044490632                                      |
| ETIM 8.0              | EC000261   |
| Product End of Life   | It does not require specific recycling operations. |
| Product Type          | Wall-mounting Cabinet                              |

| Technical Attributes            |  |
|---------------------------------|--|
| Application                     | Industrial environments, manufacturing<br>companies requiring a high degree of protection<br>against dust, splashes and impacts. |
| Maximum Operational Voltage (V) | 1000 AC / 1500 DC  |

| Physical Attributes            |  |
|--------------------------------|--|
| Ambient Temperature Range (°C) | -25 to +60   |
| Cable Entry (mm)               | 125H x 285W  |
| Colour                         | RAL 7035   |
| Door Profiles                  | 2  |
| Door Type                      | Single   |
| Finish                         | Coated with primer, and hardened polyester paint, textured, with UV protection |
| Installation                   | Surface  |



| Lock Type                        | 5-mm double-bit lock - Two 1-point lock  |
|----------------------------------|--|
| Material                         | Cold-rolled steel EN 10130+A1  |
| Maximum Cabinet Load (kg)        | 225  |
| Maximum Door Load (kg)           | 25   |
| Maximum Mounting Plate Load (kg) | 200  |
| Mounting Plate                   | With flat mounting plate. 2-mm galvanised sheet steel  |
| No. of Hinges                    | 2  |
| No. of Locks                     | 2  |
| Sealing Gasket                   | Injected polyurethane sealing gasket   |
| Supply                           | Supplied in individual packaging containing<br>cabinet, plate and accessory bag. Mounting plate<br>is supplied unassembled inside the packaging. |
| Type of Door                     | Single opaque door. Reversible   |
| Wall Fixing (mm)                 | 260H x 260W  |

| Dimensions                 |                    |
|----------------------------|--------------------|
| Dimensions (mm)            | 600H x 400W x 200D |
| Mounting Plate Size (mm)   | 570W x 350H        |
| Thickness (mm)             | Enclosure: 1.2     |
|                            | Door: 1.2          |
|                            | Cable entry lid: 2 |
| Usable Internal Space (mm) | 550H x 350W x 179D |
| Weight (kg)                | 14.1               |

| Protection & Standards    |                        |
|---------------------------|------------------------|
| Certifications            | UL508A                 |
| Degree of Protection      | IP66                   |
| Directive                 | 2014/35/EU             |
| NEMA Degree of Protection | NEMA 1, 12, 4          |
| Rated Impact Resistance   | IK10                   |
| Standards                 | IEC 62208, IEC 61439-1 |
| Sustainability            | RoHS - REACH           |



Resources

Product catalogue (Flipbook)

Download from here