

## **Product No:LD6A-4DQB-RYSG**

## IDEC LIGHT TOWER LED 6A DIRECT MOUNT BLACK BASE - STEADY ALARM 24V AC DC LD6A-4DQB-RYSG

## **FEATURES**

- Steady
- Flashing
- Alarm



General Information	
Brand	IDEC
Product Type	Signal Light Tower

Technical Attributes	
No. of Tiers	4
Rated Insulation Voltage (V)	60
Resistance to Shock (m/s²)	147
Resistance to Vibrations	10 to 55Hz

Physical Attributes	
Housing Colour	Dark Gray
Illumination Colour	Red, Yellow, Blue, Green
Mounting Type	Direct
Operating Humidity	45 to 85%
Operational Temperature Range (°C)	-25 to 55

Dimensions	
Weight (g)	305

Protection & Standards	
Degree of Protection	IP65, IP54, IP23
Pollution Degree	3

IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > SAFETY AUTOMATION & CONTROL > SAFETY PUSHBUTTONS & OPERATOR DEVICES > IPD > AUTOMATION & CONTROL > CONTROL DEVICES > PILOT & SIGNALLING DEVICES



Resources	
Product catalogue (Flipbook)	Download from here