

Product No: F202F63/0.03

ABB RCCB 2P 63A 30mA TYPE F F202F63/0.03

FEATURES

- Protection for people and buildings against earth leakage faults
- Used where earth fault waveform may be sinusoidal or pulsating DC
- Pole configuration: 2P



General Information

| | |
|--------------|------|
| Brand | ABB |
| Product Type | RCCB |
| Series | F200 |

Technical Attributes

| | |
|--|-------|
| Net Weight (kg) | 0.2 |
| No. of Poles | 2P |
| Power Loss (W) | 3.2 |
| Rated Conditional Short-Circuit Current - Inc (kA) | 10 |
| Rated Current (A) | 63 |
| Rated Frequency (Hz) | 50/60 |
| Rated Impulse Withstand Voltage (kV) | 4 |
| Rated Insulation Voltage (V) | 500 |
| Rated Operational Voltage (V) | 230 |
| Rated Residual Current (mA) | 30 |
| Rated Voltage (V) | 230 |

Physical Attributes

| | |
|--------------------------------|-----------|
| Ambient Temperature Range (°C) | -25 to 55 |
|--------------------------------|-----------|

Dimensions

| | |
|-----------------|-----------------|
| Dimensions (mm) | 35W x 85H x 69D |
|-----------------|-----------------|

Protection & Standards

| | |
|----------------------|----------------------------|
| Degree of Protection | IP2X |
| Pollution Degree | 2 |
| Standards | IEC/EN 61008, IEC/EN 62423 |